

Flange

Technical features

INDEX TRAUB products

TNX65/42

Function (Component)

Flange

Spindle clearance

65 mm

Bar loading magazine

FMB turbo 5-65

Machining side

Main spindle

Material diameter

19 mm (0.75 ") • 20 mm (0.79 ") •
21 mm (0.83 ") • 22 mm (0.87 ") •
23 mm (0.91 ") • 24 mm (0.94 ") •
25 mm (0.98 ") • 26 mm (1.02 ") •
27 mm (1.06 ") • 28 mm (1.1 ") • 29
mm (1.14 ") • 30 mm (1.18 ") • 31
mm (1.22 ") • 32 mm (1.26 ") • 33
mm (1.30 ") • 34 mm (1.34 ") • 35
mm (1.38 ") • 36 mm (1.42 ") • 37
mm (1.46 ") • 38 mm (1.50 ") • 39
mm (1.54 ") • 40 mm (1.57 ") • 41
mm (1.61 ") • 42 mm (1.65 ") • 43
mm (1.69 ") • 44 mm (1.73 ") • 45
mm (1.77 ") • 46 mm (1.81 ") • 47
mm (1.85 ") • 48 mm (1.89 ") • 49
mm (1.93 ") • 50 mm (1.97 ") • 51
mm (2.01 ") • 52 mm (2.05 ") • 53
mm (2.09 ") • 54 mm (2.13 ") • 55
mm (2.17 ") • 56 mm (2.20 ") • 57
mm (2.24 ") • 58 mm (2.28 ") • 59
mm (2.32 ") • 60 mm (2.36 ") • 61
mm (2.40 ") • 62 mm (2.44 ") • 63
mm (2.48 ")



No 3-side view is currently available for this product

10588299
779649

INDEX

Documents

No downloads available for this product