

## Guide bushing, 11,00 - 42,00 mm

### Technical data

|                             |   |
|-----------------------------|---|
| <b>INDEX TRAUB products</b> | C100  |
| <b>Function (Component)</b> | Guide bushing   |
| <b>Spindle clearance</b>    | 42mm • 65mm   |
| <b>Bar loading magazine</b> | INDEX MBL • INDEX MBF   |
| <b>Clamping stroke</b>      | 7mm (0.28") • 12.5mm (0.49") •<br>20mm (0.79")  |
| <b>Machining side</b>       | Main spindle  |
| <b>Material diameter</b>    | 11mm (0.43") • 12mm (0.47") •<br>13mm (0.51") • 14mm (0.55") •<br>15mm (0.59") • 16mm (0.63") •<br>17mm (0.67") • 18mm (0.71") •<br>19mm (0.75") • 20mm (0.79") •<br>21mm (0.83") • 22mm (0.87") •<br>23mm (0.91") • 24mm (0.94") •<br>25mm (0.98") • 26mm (1.02") •<br>27mm (1.06") • 28mm (1.1") •<br>29mm (1.14") • 30mm (1.18") •<br>31mm (1.22") • 32mm (1.26") •<br>33mm (1.30") • 34mm (1.34") •<br>35mm (1.38") • 36mm (1.42") •<br>37mm (1.46") • 38mm (1.50") •<br>39mm (1.54") • 40mm (1.57") •<br>41mm (1.61") • 42mm (1.65") |

No 3-side view is currently available for this product

## **Documents**

No downloads available for this product