

Flange

Technical data

INDEX TRAUB products

TNX65/42

Function (Component)

Flange

Spindle clearance

65mm

Bar loading magazine

FMB turbo 5-65

Machining side

Main spindle

Material diameter

19mm (0.75") • 20mm (0.79") •
21mm (0.83") • 22mm (0.87") •
23mm (0.91") • 24mm (0.94") •
25mm (0.98") • 26mm (1.02") •
27mm (1.06") • 28mm (1.1") •
29mm (1.14") • 30mm (1.18") •
31mm (1.22") • 32mm (1.26") •
33mm (1.30") • 34mm (1.34") •
35mm (1.38") • 36mm (1.42") •
37mm (1.46") • 38mm (1.50") •
39mm (1.54") • 40mm (1.57") •
41mm (1.61") • 42mm (1.65") •
43mm (1.69") • 44mm (1.73") •
45mm (1.77") • 46mm (1.81") •
47mm (1.85") • 48mm (1.89") •
49mm (1.93") • 50mm (1.97") •
51mm (2.01") • 52mm (2.05") •
53mm (2.09") • 54mm (2.13") •
55mm (2.17") • 56mm (2.20") •
57mm (2.24") • 58mm (2.28") •
59mm (2.32") • 60mm (2.36") •
61mm (2.40") • 62mm (2.44") •
63mm (2.48")



No 3-side view is currently available for this product

10588299
779649

INDEX

Documents

No downloads available for this product