

**INDEX**

**TRAUB**



**INDEX B400  
TRAUB TNA400.2**

**Radial turret VDI40**

Tool holder      Overview

## **Note on applicability**


Illustrations in this publication may deviate from the product supplied. Errors and omissions due to technical progress expected.

## **A word on copyright**

This document is protected by copyright and was originally compiled in German.


The duplication and distribution of this document or parts thereof is prohibited without prior consent of the copyright owner, and any violators will be prosecuted. All rights, including the right to translate, are reserved.

© Copyright by INDEX-Werke GmbH & Co. KG




**10875475 Bar stop, live**

<b>Fixation</b>	none
<b>Mounting</b>	D25 (0.98 ")
<b>Cooling</b>	–
<b>X / Y / Z</b>	90 (3.54) / – / 1 (0.04) mm (")




**10900227 Bar stop, live**

<b>Fixation</b>	–
<b>Mounting</b>	D58 (2.28 ")
<b>Cooling</b>	–
<b>X / Y / Z</b>	– / – / 30 (1.18) mm (")




**10452051 Bar stop, live**

<b>Fixation</b>	–
<b>Mounting</b>	D85 (3.35 ")
<b>Cooling</b>	–
<b>X / Y / Z</b>	– / – / 30 (1.18) mm (")




**10426764 Compensation holder**

<b>Fixation</b>	W serration
<b>Mounting</b>	VDI 30
<b>Cooling</b>	external and internal, p <sub>max</sub> 20 bar
<b>X / Y / Z</b>	90 (3.54) / – / 2 (0.08) mm (")




**12103053 Compensation holder**

<b>Fixation</b>	W serration
<b>Mounting</b>	VDI 30
<b>Cooling</b>	external and internal, p <sub>max</sub> 80 bar
<b>X / Y / Z</b>	110 (4.33) / – / 10 (0.39) mm (")



**10494964 Compensation holder**

<b>Fixation</b>	W serration
<b>Mounting</b>	VDI 40
<b>Cooling</b>	external and internal, p <sub>max</sub> 20 bar
<b>X / Y / Z</b>	90 (3.54) / – / 5 (0.20) mm (")




**12089680 Compensation holder**

<b>Fixation</b>	W serration
<b>Mounting</b>	VDI 40
<b>Cooling</b>	external and internal, p <sub>max</sub> 80 bar
<b>X / Y / Z</b>	110 (4.33) / – / 10 (0.39) mm (")


# Stationary tool holder Radial turret Shank VDI40

INDEX TRAUB




## 10141629 Drilling tool holder

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 40
<b>Cooling</b>	external, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	90 (3.54) / - / 49 (1.93) mm (")




## 10829165 Drilling tool holder

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 40
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	110 (4.33) / - / 49 (1.93) mm (")




## 10142897 Drilling tool holder

<b>Fixation</b>	W serration
<b>Mounting</b>	DIN 1835 B/E D32 (1.26 ")
<b>Cooling</b>	external and internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	100 (3.94) / - / 30 (1.18) mm (")




## 10173165 Drilling tool holder

<b>Fixation</b>	W serration
<b>Mounting</b>	DIN 1835 B/E D32 (1.26 ")
<b>Cooling</b>	external and internal, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	100 (3.94) / - / 4 (0.16) mm (")




## 12021948 Drilling tool holder

<b>Fixation</b>	W serration
<b>Mounting</b>	DIN 1835 B/E D40 (1.57 ")
<b>Cooling</b>	external and internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	90 (3.54) / - / 45 (1.77) mm (")




## 12026397 Drilling tool holder

<b>Fixation</b>	W serration
<b>Mounting</b>	D25 (0.98 ")
<b>Cooling</b>	external and internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	110 (4.33) / - / 57.5 (2.26) mm (")




## 12026368 Drilling tool holder

<b>Fixation</b>	W serration
<b>Mounting</b>	D32 (1.26 ")
<b>Cooling</b>	external and internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	110 (4.33) / - / 57.5 (2.26) mm (")




**12036278 Drilling tool holder**

<b>Fixation</b>	W serration
<b>Mounting</b>	D32 (1.26 ")
<b>Cooling</b>	external and internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	110 (4.33) / - / - mm (")




**12100635 Drilling tool holder**

<b>Fixation</b>	W serration
<b>Mounting</b>	D32 (1.26 ")
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>X / Y / Z</b>	110 (4.33) / 40 (1.57) / 60 (2.36) mm (")




**12102981 Drilling tool holder**

<b>Fixation</b>	W serration
<b>Mounting</b>	D40 (1.57 ")
<b>Cooling</b>	external and internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	110 (4.33) / - / 0 () mm (")




**10009218 Turning tool holder, Form C2/C3**

<b>Fixation</b>	none
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external, $p_{max}$ 20 bar
<b>X / Y / Z</b>	60 (2.36) / - / 47.5 (1.87) mm (")




**10464052 Turning tool holder, Form C1/C4**

<b>Fixation</b>	none
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external, $p_{max}$ 20 bar
<b>X / Y / Z</b>	60 (2.36) / - / 47.5 (1.87) mm (")




**10810887 Turning tool holder, Form C2/C3**

<b>Fixation</b>	none
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external, $p_{max}$ 20 bar
<b>X / Y / Z</b>	85 (3.35) / - / 47.5 (1.87) mm (")




**10883332 Turning tool holder, double**

<b>Fixation</b>	none
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external, $p_{max}$ 20 bar
<b>X / Y / Z</b>	85 (3.35) / - / 47.5 (1.87) mm (")




**10965815 Turning tool holder, Form C1/C4**

<b>Fixation</b>	none
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	85 (3.35) / - / 42.5 (1.67) mm (")




**10105290 Turning tool holder, double**

<b>Fixation</b>	W serration
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	85 (3.35) / - / 47.5 (1.87) mm (")




**12077312 Turning tool holder, Form C1/C4**

<b>Fixation</b>	W serration
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external and internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	60.6 (2.39) / - / 47.5 (1.87) mm (")




**12098663 Turning tool holder, Form C2/C3**

<b>Fixation</b>	W serration
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external and internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	60.6 (2.39) / - / 47.5 (1.87) mm (")




**12101123 Turning tool holder, double**

<b>Fixation</b>	W serration
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external and internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	90 (3.54) // 50 (1.97) mm (")



**10011449 Turning tool holder, Form C1/C4**

<b>Fixation</b>	none
<b>Mounting</b>	square 32x32
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	80 (3.15) / - / 51.5 (2.03) mm (")




**10730998 Turning tool holder, Form C2/C3**

<b>Fixation</b>	none
<b>Mounting</b>	square 32x32
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	83 (3.27) / - / 51.5 (2.03) mm (")


# Stationary tool holder Radial turret Shank VDI40

INDEX TRAUB




## 10107867 Turning tool holder, Form C1/C4

<b>Fixation</b>	W serration
<b>Mounting</b>	square 32x32
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	80.6 (3.17) / - / 51.5 (2.03) mm (")




## 10521839 Turning tool holder, Form C2/C3

<b>Fixation</b>	W serration
<b>Mounting</b>	square 32x32
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	80.6 (3.17) / - / 51.5 (2.03) mm (")




## 10135121 Turning tool holder, Form B1/B4

<b>Fixation</b>	none
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	76 (2.99) / - / 42.5 (1.67) mm (")




## 10551035 Turning tool holder, Form B2/B3

<b>Fixation</b>	none
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	76 (2.99) / - / 42.5 (1.67) mm (")




## 10547558 Turning tool holder

<b>Fixation</b>	W serration
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	105 (4.13) / - / 42.5 (1.67) mm (")




## 12099012 Turning tool holder, Form B1/B4

<b>Fixation</b>	W serration
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external and internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	44 (1.73) / - / 40 (1.57) mm (")




## 12099016 Turning tool holder, Form B1/B4

<b>Fixation</b>	W serration
<b>Mounting</b>	square 25x25
<b>Cooling</b>	external and internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	104 (4.09) / - / 40 (1.57) mm (")




**12099018 Turning tool holder, Form B1/B4**

<b>Fixation</b>	W serration
<b>Mounting</b>	square 32x32
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>X / Y / Z</b>	56 (2.20) / - / 40 (1.57) mm (")




**12099020 Turning tool holder, Form B1/B4**

<b>Fixation</b>	W serration
<b>Mounting</b>	square 32x32
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>X / Y / Z</b>	105 (4.13) / - / 40 (1.57) mm (")




**10781727 Basic holder**

<b>Fixation</b>	W serration
<b>Mounting</b>	INDEX TRAUB CAPTO C5
<b>Cooling</b>	internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	75 (2.95) / - / 20 (0.79) mm (")




**10846334 Basic holder, vertically adjustable**

<b>Fixation</b>	W serration
<b>Mounting</b>	-
<b>Cooling</b>	internal
<b>X / Y / Z</b>	17 (0.67) / - / 34.8 (1.37) mm (")




**10011884 Grooving tool holding block**

<b>Fixation</b>	-
<b>Mounting</b>	Trapezoid 32x4
<b>Cooling</b>	internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	87.5 (3.44) / - / 6.5 (0.26) mm (")



**10453502 Grooving tool holding block**

<b>Fixation</b>	-
<b>Mounting</b>	Trapezoid 32x4
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>X / Y / Z</b>	87.5 (3.44) / - / 20 (0.79) mm (")




**10890955 Grooving tool holding block**

<b>Fixation</b>	-
<b>Mounting</b>	Trapezoid 32x4
<b>Cooling</b>	external and internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	87.5 (3.44) / - / 15 (0.59) mm (")


# Stationary tool holder Radial turret Shank VDI40

INDEX 




## 10908238 Grooving tool holding block

<b>Fixation</b>	–
<b>Mounting</b>	Trapezoid 32x4
<b>Cooling</b>	external and internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	87.5 (3.44) / – / 20 (0.79) mm (")




## 10629246 Grooving tool holding block

<b>Fixation</b>	–
<b>Mounting</b>	Trapezoid 32x5
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>X / Y / Z</b>	87.5 (3.44) / – / 7 (0.28) mm (")




## 10139337 Grooving tool holding block

<b>Fixation</b>	–
<b>Mounting</b>	Trapezoid 32x8
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>X / Y / Z</b>	87.5 (3.44) / – / 7 (0.28) mm (")




## 10513139 Grooving tool holding block

<b>Fixation</b>	–
<b>Mounting</b>	Trapezoid 32x8
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>X / Y / Z</b>	87.5 (3.44) / – / 15 (0.59) mm (")




## 10694590 Grooving tool holding block

<b>Fixation</b>	–
<b>Mounting</b>	Trapezoid 32x8
<b>Cooling</b>	external and internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	87.5 (3.44) / – / 7 (0.28) mm (")




## 12092672 Grooving tool holding block

<b>Fixation</b>	–
<b>Mounting</b>	Trapezoid 32x8
<b>Cooling</b>	external and internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	87.5 (3.44) / – / 20 (0.79) mm (")




## 12092674 Grooving tool holding block

<b>Fixation</b>	–
<b>Mounting</b>	Trapezoid 32x8
<b>Cooling</b>	external and internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	107.5 (4.23) / – / 7 (0.28) mm (")




**10351552 Basic holder**

<b>Fixation</b>	W serration
<b>Mounting</b>	INDEX TRAUB CAPTO C5
<b>Cooling</b>	internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	110 (4.33) / - / 20 (0.79) mm (")




**10330602 Embossing roll holder**

<b>Fixation</b>	none
<b>Mounting</b>	-
<b>Cooling</b>	-
<b>X / Y / Z</b>	79 (3.11) / - / 46 (1.81) mm (")




**10429774 Embossing roll holder**

<b>Fixation</b>	none
<b>Mounting</b>	-
<b>Cooling</b>	-
<b>X / Y / Z</b>	75 (2.95) / - / 67.5 (2.66) mm (")




**10363269 Workpiece holder, adjustable**

<b>Fixation</b>	none
<b>Mounting</b>	D30-200 (2.01 "-7.60 ")
<b>Cooling</b>	-
<b>X / Y / Z</b>	115.5 (4.55) / - / - mm (")




**11068927 Calibrating tool**

<b>Fixation</b>	none
<b>Mounting</b>	-
<b>Cooling</b>	-
<b>X / Y / Z</b>	100 (3.94) / - / - mm (")



**10241951 Coolant nozzle**

<b>Fixation</b>	none
<b>Mounting</b>	-
<b>Cooling</b>	external, $p_{max}$ 40 bar
<b>X / Y / Z</b>	15 (0.59) / - / - mm (")




**10410109 Coolant nozzle**

<b>Fixation</b>	none
<b>Mounting</b>	-
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>X / Y / Z</b>	25 (0.98) / - / - mm (")


**Stationary tool holder  
Radial turret Shank VDI40**

**INDEX TRAUB**




**10573819 Blanking plug**

<b>Fixation</b>	—
<b>Mounting</b>	—
<b>Cooling</b>	—
<b>X / Y / Z</b>	10 (0.39) / – / – mm (")




**10806502 Drilling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 20
<b>Cooling</b>	external and internal, $p_{max}$ 80 bar
<b>Speed ratio</b>	1:2 (0.5)
<b>X / Y / Z</b>	92 (3.62) / - / 35 (1.38) mm (")




**10015358 Drilling unit**

<b>Fixation</b>	none
<b>Mounting</b>	ER 25
<b>Cooling</b>	internal, $p_{max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	86 (3.39) / - / - mm (")




**10182305 Drilling unit**

<b>Fixation</b>	none
<b>Mounting</b>	ER 25
<b>Cooling</b>	external, $p_{max}$ 40 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	54 (2.13) / - / - mm (")




**12027363 Drilling unit**

<b>Fixation</b>	none
<b>Mounting</b>	ER 25
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	/ - / - mm (")




**10689484 Drilling unit**

<b>Fixation</b>	none
<b>Mounting</b>	DIN 1835 B/E D20 (0.79 ")
<b>Cooling</b>	external, $p_{max}$ 40 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	67 (2.64) / - / - mm (")




**12030161 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 25
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>Speed ratio</b>	1:2 (0.5)
<b>X / Y / Z</b>	99 (3.9) / - / 43 (1.69) mm (")




**12030959 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 25
<b>Cooling</b>	internal, $p_{max}$ 80 bar
<b>Speed ratio</b>	1:2 (0.5)
<b>X / Y / Z</b>	99 (3.9) / - / 43 (1.69) mm (")




**12029035 Milling unit**

<b>Fixation</b>	none
<b>Mounting</b>	ER 25
<b>Cooling</b>	external, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	76 (2.99) / - / - mm (")




**12088208 Milling unit**

<b>Fixation</b>	none
<b>Mounting</b>	ER 32
<b>Cooling</b>	external, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	82 (3.23) / - / - mm (")




**12038383 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 32
<b>Cooling</b>	internal, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	114.5 (4.51) / - / 46 (1.81) mm (")




**12038387 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 32
<b>Cooling</b>	external, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	114.5 (4.51) / - / 46 (1.81) mm (")




**12037366 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 32
<b>Cooling</b>	internal, $p_{\max}$ 80 bar
<b>Speed ratio</b>	2:1 (2)
<b>X / Y / Z</b>	114.5 (4.51) / - / 46 (1.81) mm (")




**12038379 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 32
<b>Cooling</b>	external, $p_{\max}$ 80 bar
<b>Speed ratio</b>	2:1 (2)
<b>X / Y / Z</b>	114.5 (4.51) / - / 46 (1.81) mm (")




**12029031 Milling unit**

<b>Fixation</b>	none
<b>Mounting</b>	D25 (0.98 ")
<b>Cooling</b>	external, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	85 (3.35) / - / - mm (")




**12028521 Milling unit**

<b>Fixation</b>	none
<b>Mounting</b>	D32 (1.26 ")
<b>Cooling</b>	external, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	85 (3.35) / - / - mm (")




**10555168 Drilling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 20
<b>Cooling</b>	external, internal optional, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:3 (0.333)
<b>X / Y / Z</b>	110 (4.33) / - / 96 (3.78) mm (")




**10761117 Drilling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 20
<b>Cooling</b>	external, internal optional, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:3 (0.333)
<b>X / Y / Z</b>	90 (3.54) / - / 96 (3.78) mm (")




**10394693 Drilling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 25
<b>Cooling</b>	external, internal optional, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:2 (0.5)
<b>X / Y / Z</b>	110 (4.33) / - / 97 (3.82) mm (")




**11064601 Drilling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 25
<b>Cooling</b>	external, internal optional, $p_{\max}$ 80 bar
<b>Speed ratio</b>	1:2 (0.5)
<b>X / Y / Z</b>	90 (3.54) / - / 97 (3.82) mm (")




**10217936 Drilling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	Hydraulic expansion chuck D20
<b>Cooling</b>	internal, $p_{\max}$ 20 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	90 (3.54) / - / 88 (3.46) mm (")




**10340247 Drilling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	Hydraulic expansion chuck D20
<b>Cooling</b>	internal, external optional, $p_{\max}$ 20 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	90 (3.54) / - / 96.5 (3.80) mm (")




**12033177 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 32
<b>Cooling</b>	external, internal optional, $p_{max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	110 (4.33) / - / 93.5 (3.68) mm (")




**12042168 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 32
<b>Cooling</b>	external, internal optional, $p_{max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	110 (4.33) / - / 49.5 (1.95) mm (")




**10788622 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 32
<b>Cooling</b>	external, internal optional, $p_{max}$ 80 bar
<b>Speed ratio</b>	2:1 (2)
<b>X / Y / Z</b>	110 (4.33) / - / 93.5 (3.68) mm (")




**12042169 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 32
<b>Cooling</b>	external, $p_{max}$ 80 bar
<b>Speed ratio</b>	2:1 (2)
<b>X / Y / Z</b>	110 (4.33) / - / 49.5 (1.95) mm (")




**10744754 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 40
<b>Cooling</b>	external, internal optional, $p_{max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	110 (4.33) / - / mm (")




**12033082 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 40
<b>Cooling</b>	external, internal optional, $p_{max}$ 80 bar
<b>Speed ratio</b>	2:1 (2)
<b>X / Y / Z</b>	110 (4.33) / - / mm (")




**12032576 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	D32 (1.26 ")
<b>Cooling</b>	external, internal optional, $p_{max}$ 80 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	110 (4.33) / - / 100 (3.94) mm (")




**12032524 Milling unit**

<b>Fixation</b>	W serration
<b>Mounting</b>	D32 (1.26 ")
<b>Cooling</b>	external, internal optional, $p_{max}$ 80 bar
<b>Speed ratio</b>	2:1 (2)
<b>X / Y / Z</b>	110 (4.33) / - / 100 (3.94) mm (")




**10978445 Drilling unit, angle-adjustable**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 16
<b>Cooling</b>	external, $p_{max}$ 40 bar
<b>Speed ratio</b>	1:1 (1)
<b>X / Y / Z</b>	65 (2.56) / - / - mm (")




**12054788 Fluid spindle, up to 55.000 rpm**

<b>Fixation</b>	W serration
<b>Mounting</b>	ER 11
<b>Cooling</b>	external, $p_{max}$ 40 bar
<b>X / Y / Z</b>	110 (4.33) / - / 75.6 (2.98) mm (")




**10428174 Bar stop, adjustable, live**

<b>Fixation</b>	none
<b>Mounting</b>	–
<b>Cooling</b>	–
<b>X / Y / Z</b>	60 - 97 (2.36 - 3.82) / – / – mm (")




**10679593 Bar stop, adjustable, live**

<b>Fixation</b>	none
<b>Mounting</b>	–
<b>Cooling</b>	–
<b>X / Y / Z</b>	60 - 97 (2.36 - 3.82) / – / – mm (")




**10424888 Drilling tool holder, Form E4**

<b>Fixation</b>	none
<b>Mounting</b>	ER 25
<b>Cooling</b>	internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	68 (2.68) / – / – mm (")




**10453838 Drilling tool holder, Form E4**

<b>Fixation</b>	none
<b>Mounting</b>	ER 32
<b>Cooling</b>	internal, $p_{max}$ 20 bar
<b>X / Y / Z</b>	76 (2.99) / – / – mm (")




**10239645 Drilling tool holder, Form E4**

<b>Fixation</b>	none
<b>Mounting</b>	ER 40
<b>Cooling</b>	internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	80 (3.15) / – / – mm (")




**10502799 Drilling tool holder, Form E1**

<b>Fixation</b>	none
<b>Mounting</b>	DIN 1835 E D20 (0.79 ")
<b>Cooling</b>	internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	67 (2.64) / – / – mm (")




**10659026 Drilling tool holder, Form E1**

<b>Fixation</b>	none
<b>Mounting</b>	DIN 1835 E D25 (0.98 ")
<b>Cooling</b>	internal, $p_{max}$ 80 bar
<b>X / Y / Z</b>	71 (2.80) / – / – mm (")




**10168049 Drilling tool holder, Form E2**

<b>Fixation</b>	none
<b>Mounting</b>	D8 (0.31 ")
<b>Cooling</b>	external and internal, $p_{max}$ 20 bar
<b>X / Y / Z</b>	60 (2.36) / - / - mm (")




**10364335 Drilling tool holder, Form E2**

<b>Fixation</b>	none
<b>Mounting</b>	D10 (0.39 ")
<b>Cooling</b>	external and internal, $p_{max}$ 20 bar
<b>X / Y / Z</b>	60 (2.36) / - / - mm (")




**10240059 Drilling tool holder, Form E2**

<b>Fixation</b>	none
<b>Mounting</b>	D12 (0.47 ")
<b>Cooling</b>	external and internal, $p_{max}$ 20 bar
<b>X / Y / Z</b>	60 (2.36) / - / - mm (")




**11043672 Drilling tool holder, Specially for the marking tool WriteStar**

<b>Fixation</b>	none
<b>Mounting</b>	D12 (0.47 ")
<b>Cooling</b>	-
<b>X / Y / Z</b>	68 (2.68) / - / - mm (")




**10298106 Drilling tool holder, Form E2**

<b>Fixation</b>	none
<b>Mounting</b>	D16 (0.63 ")
<b>Cooling</b>	external and internal, $p_{max}$ 20 bar
<b>X / Y / Z</b>	60 (2.36) / - / - mm (")




**10806859 Drilling tool holder, Form E2**

<b>Fixation</b>	none
<b>Mounting</b>	D20 (0.79 ")
<b>Cooling</b>	external and internal, $p_{max}$ 20 bar
<b>X / Y / Z</b>	60 (2.36) / - / - mm (")




**10040148 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	D25 (0.98 ")
<b>Cooling</b>	external and internal, $p_{max}$ 40 bar
<b>X / Y / Z</b>	45 (1.77) / - / - mm (")




**10175060 Drilling tool holder, Form E2**

<b>Fixation</b>	none
<b>Mounting</b>	D25 (0.98 ")
<b>Cooling</b>	external and internal, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	60 (2.36) / - / - mm (")




**10601688 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	D32 (1.26 ")
<b>Cooling</b>	internal, $p_{\max}$ 80 bar
<b>X / Y / Z</b>	73 (2.87) / - / - mm (")




**11055569 Drilling tool holder, Form E2**

<b>Fixation</b>	none
<b>Mounting</b>	D32 (1.26 ")
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	70 (2.76) / - / - mm (")




**10631335 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	MK1
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	30 (1.18) / - / - mm (")




**10550804 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	MK2
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	27 (1.06) / - / - mm (")




**10677499 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	MK3
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	45 (1.77) / - / - mm (")




**10217247 Basic holder, vertically adjustable**

<b>Fixation</b>	none
<b>Mounting</b>	-
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	14 (0.55) / - / - mm (")




**10374519 Drill holding block**

<b>Fixation</b>	–
<b>Mounting</b>	ER 25
<b>Cooling</b>	–, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	30 (1.18) / – / – mm (")




**10387522 Center holder, elastic, live**

<b>Fixation</b>	none
<b>Mounting</b>	D15.4 (0.61")/Cone 1:7.5
<b>Cooling</b>	–
<b>X / Y / Z</b>	68.5 (2.70) / – / – mm (")




**10593935 Center holder, live**

<b>Fixation</b>	none
<b>Mounting</b>	D15.4 (0.61")/Cone 1:7.5
<b>Cooling</b>	–
<b>X / Y / Z</b>	69.5 (2.74) / – / – mm (")




**10301384 Tapping tool holder, extendable**

<b>Fixation</b>	none
<b>Mounting</b>	D25 (0.98")
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	73 (2.87) / – / – mm (")




**10894326 Reaming tool holder, adjustable**

<b>Fixation</b>	none
<b>Mounting</b>	ER 25
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	73.5 (2.89) / – / – mm (")




**11041243 Reaming tool holder, adjustable**

<b>Fixation</b>	none
<b>Mounting</b>	D18 (0.71")
<b>Cooling</b>	external, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	59 (2.32) / – / – mm (")



**10459517 Reaming tool holder, self-centering**


<b>Fixation</b>	none
<b>Mounting</b>	D20 (0.79")
<b>Cooling</b>	internal, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	93 (3.66) / – / – mm (")



**10929722 Broaching/ Slotting holder, rotating, live**


**Fixation** none  
**Mounting** D12 (0.47 ")  
**Cooling** external,  $p_{\max}$  20 bar  
**X / Y / Z** 60 (2.36) / - / - mm (")

---




**11005033 Drilling tool holder, Form E4**

<b>Fixation</b>	none
<b>Mounting</b>	ER 32
<b>Cooling</b>	internal, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	85 (3.35) / - / - mm (")




**10818472 Drilling tool holder, Form E4**

<b>Fixation</b>	none
<b>Mounting</b>	ER 40
<b>Cooling</b>	internal, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	80 (3.15) / - / - mm (")




**10683918 Drilling tool holder, Form E1**

<b>Fixation</b>	none
<b>Mounting</b>	DIN 1835 B/E D16 (0.63 ")
<b>Cooling</b>	internal, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	67 (2.64) / - / - mm (")




**10295079 Drilling tool holder, Form E1**

<b>Fixation</b>	none
<b>Mounting</b>	DIN 1835 B/E D20 (0.79 ")
<b>Cooling</b>	internal, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	67 (2.64) / - / - mm (")




**10195001 Drilling tool holder, Form E1**

<b>Fixation</b>	none
<b>Mounting</b>	DIN 1835 B/E D25 (0.98 ")
<b>Cooling</b>	internal, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	75 (2.95) / - / - mm (")




**10944270 Drilling tool holder, Form E1**

<b>Fixation</b>	none
<b>Mounting</b>	DIN 1835 B/E D32 (1.26 ")
<b>Cooling</b>	internal, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	75 (2.95) / - / - mm (")




**10792184 Drilling tool holder, Form E1**

<b>Fixation</b>	none
<b>Mounting</b>	DIN 1835 B/E D40 (1.57 ")
<b>Cooling</b>	internal, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	90 (3.54) / - / - mm (")




**10666791 Drilling tool holder, Specially for the marking tool WriteStar**

<b>Fixation</b>	none
<b>Mounting</b>	D12 (0.47 ")
<b>Cooling</b>	–
<b>X / Y / Z</b>	68 (2.68) / – / – mm (")




**10046170 Drilling tool holder, Form E2**

<b>Fixation</b>	none
<b>Mounting</b>	D40 (1.57 ")
<b>Cooling</b>	external, $p_{max}$ 20 bar
<b>X / Y / Z</b>	85 (3.35) / – / – mm (")




**11013124 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	D40 (1.57 ")
<b>Cooling</b>	external, $p_{max}$ 20 bar
<b>X / Y / Z</b>	85 (3.35) / – / 10 (0.39) mm (")




**11018965 Drilling tool holder, Form E2**

<b>Fixation</b>	none
<b>Mounting</b>	D40 (1.57 ")
<b>Cooling</b>	external and internal, $p_{max}$ 40 bar
<b>X / Y / Z</b>	90 (3.54) / – / – mm (")




**10004799 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	D50 (1.97 ")
<b>Cooling</b>	external, $p_{max}$ 20 bar
<b>X / Y / Z</b>	125 (4.92) / – / – mm (")




**10268157 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	MK2
<b>Cooling</b>	internal, $p_{max}$ 20 bar
<b>X / Y / Z</b>	36 (1.42) / – / – mm (")




**10943551 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	MK3
<b>Cooling</b>	internal, $p_{max}$ 20 bar
<b>X / Y / Z</b>	36 (1.42) / – / – mm (")




**10502684 Drilling tool holder**

<b>Fixation</b>	none
<b>Mounting</b>	MK4
<b>Cooling</b>	internal, $p_{\max}$ 20 bar
<b>X / Y / Z</b>	80 (3.15) / - / - mm (")



**10708899 Center holder, live**

<b>Fixation</b>	none
<b>Mounting</b>	D15.4 (0.61")/Cone 1:7.5
<b>Cooling</b>	-
<b>X / Y / Z</b>	65 (2.56) / - / - mm (")



**10792376 Reaming tool holder, adjustable**

<b>Fixation</b>	none
<b>Mounting</b>	DIN 1835 B/E D20 (0.79")
<b>Cooling</b>	internal, $p_{\max}$ 40 bar
<b>X / Y / Z</b>	78 (3.07) / - / - mm (")

**INDEX** **TRAUB**

**INDEX** **TRAUB**

**INDEX** **TRAUB**



DAW021EN - 20161620 10.21 Printed in Germany Subject to change without prior notice

**INDEX-Werke GmbH & Co. KG  
Hahn & Tessky**

Plochinger Straße 92  
D-73730 Esslingen

Fon +49 711 3191-0  
Fax +49 711 3191-587

[info@index-werke.de](mailto:info@index-werke.de)  
[www.index-werke.de](http://www.index-werke.de)