



INDEX ABC

Tool holder

Overview


Note on applicability

Illustrations in this publication may deviate from the product supplied. Errors and omissions due to technical progress expected.

A word on copyright


This document is protected by copyright and was originally compiled in German. The duplication and distribution of this document or parts thereof is prohibited without prior consent of the copyright owner, and any violators will be prosecuted. All rights, including the right to translate, are reserved.

© Copyright by INDEX-Werke GmbH & Co. KG




10505133 Bar stop, live

Fixation	none
Mounting	D25 (0.98 ")
Cooling	–
X / Y / Z	70 (2.76) / – / 30 (1.18) mm (")




10900227 Bar stop, live

Fixation	–
Mounting	D58 (2.28 ")
Cooling	–
X / Y / Z	– / – / 30 (1.18) mm (")




10452051 Bar stop, live

Fixation	–
Mounting	D85 (3.35 ")
Cooling	–
X / Y / Z	– / – / 30 (1.18) mm (")




10558089 Compensation holder

Fixation	W serration
Mounting	VDI 20
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	70 (2.76) / – / 2 (0.08) mm (")




10592401 Compensation holder

Fixation	Vee bar
Mounting	VDI 20
Cooling	external and internal, p_{max} 40 bar
X / Y / Z	60 (2.36) / – / 2 (0.08) mm (")




10670405 Compensation holder

Fixation	Vee bar
Mounting	VDI 20
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	70 (2.76) / – / 2 (0.08) mm (")




10845238 Compensation holder

Fixation	W serration
Mounting	VDI 25
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	70 (2.76) / – / 2 (0.08) mm (")




10849685 Compensation holder

Fixation Vee bar
Mounting VDI 25
Cooling internal, p_{\max} 80 bar
X / Y / Z 70 (2.76) / - / 2 (0.08) mm (")




10054233 Compensation holder

Fixation W serration
Mounting VDI 30
Cooling external and internal, p_{\max} 20 bar
X / Y / Z 70 (2.76) / - / 2 (0.08) mm (")




10660913 Compensation holder, vertically adjustable

Fixation W serration
Mounting VDI 30
Cooling internal, p_{\max} 80 bar
X / Y / Z 70 (2.76) / - / -5 (-0.20) mm (")




10564702 Compensation holder

Fixation Vee bar
Mounting VDI 30
Cooling internal, p_{\max} 80 bar
X / Y / Z 70 (2.76) / - / -5 (-0.20) mm (")




10404809 Compensation holder

Fixation Vee bar
Mounting D1"
Cooling external, p_{\max} 80 bar
X / Y / Z 60 (2.36) / - / 15 (0.59) mm (")



10428102 Compensation holder


Fixation W serration
Mounting ABS 50
Cooling internal, p_{\max} 80 bar
X / Y / Z 70 (2.76) / - / -8 (-0.31) mm (")



10773801 Drilling tool holder, Specially for the marking tool WriteStar


Fixation none
Mounting D12 (0.47 ")
Cooling -
X / Y / Z 68 (2.68) / - / - mm (")

Stationary tool holder Shank VDI25




10265902 Drilling tool holder

Fixation	W serration
Mounting	INDEX TRAUB CAPTO C3
Cooling	internal, p_{\max} 80 bar
X / Y / Z	60 (2.36) / – / 16 (0.63) mm (")




10950356 Drilling tool holder

Fixation	Vee bar
Mounting	ER 16
Cooling	external, p_{\max} 20 bar
X / Y / Z	60 (2.36) / – / – mm (")




10545041 Drilling tool holder

Fixation	W serration
Mounting	ER 25
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	70 (2.76) / – / 31 (1.22) mm (")




10873055 Drilling tool holder

Fixation	W serration
Mounting	ER 25
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	60 (2.36) / – / 31 (1.22) mm (")




10767879 Drilling tool holder

Fixation	Vee bar
Mounting	ER 25
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	60 (2.36) / – / 31 (1.22) mm (")



10837952 Drilling tool holder


Fixation	Vee bar
Mounting	ER 25
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	70 (2.76) / – / 31 (1.22) mm (")



10306255 Drilling tool holder


Fixation	W serration
Mounting	ER 32
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	60 (2.36) / – / 52 (2.05) mm (")

Stationary tool holder Shank VDI25




10569878 Drilling tool holder

Fixation	W serration
Mounting	ER 32
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	70 (2.76) / – / 52 (2.05) mm (")




10603828 Drilling tool holder

Fixation	Vee bar
Mounting	ER 32
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	60 (2.36) / – / 52 (2.05) mm (")




10507494 Drilling tool holder

Fixation	W serration
Mounting	ER 40
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	70 (2.76) / – / 57.5 (2.26) mm (")




10057365 Drilling tool holder

Fixation	Vee bar
Mounting	ER 40
Cooling	external and internal, p_{max} 40 bar
X / Y / Z	70 (2.76) / – / 55 (2.17) mm (")




10648867 Drilling tool holder, vertically adjustable

Fixation	Vee bar
Mounting	DIN 1835 B/E D16 (0.63 ")
Cooling	internal, p_{max} 80 bar
X / Y / Z	70 (2.76) / – / 25 (0.98) mm (")



10185704 Drilling tool holder


Fixation	W serration
Mounting	DIN 1835 B/E D32 (1.26 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	60 (2.36) / – / 30 (1.18) mm (")



10712278 Drilling tool holder


Fixation	W serration
Mounting	DIN 1835 B/E D32 (1.26 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	70 (2.76) / – / 30 (1.18) mm (")

Stationary tool holder Shank VDI25




10894414 Drilling tool holder

Fixation	W serration
Mounting	DIN 1835 B/E D32 (1.26 ")
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	70 (2.76) / - / - mm (")




11020232 Drilling tool holder

Fixation	W serration
Mounting	DIN 1835 B/E D32 (1.26 ")
Cooling	external, p_{\max} 80 bar
X / Y / Z	70 (2.76) / - / 30 (1.18) mm (")




10735514 Drilling tool holder

Fixation	Vee bar
Mounting	DIN 1835 B/E D32 (1.26 ")
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	60 (2.36) / - / 30 (1.18) mm (")




10017019 Drilling tool holder

Fixation	W serration
Mounting	DIN 1835 B/E D 1 1/4"
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	70 (2.76) / - / 30 (1.18) mm (")




10954878 Drilling tool holder

Fixation	Vee bar
Mounting	D12 (0.47 ")
Cooling	external and internal, p_{\max} 20 bar
X / Y / Z	70 (2.76) / - / 30 (1.18) mm (")



10823660 Drilling tool holder, vertically adjustable


Fixation	Setting gauge
Mounting	D16 (0.63 ")
Cooling	internal, p_{\max} 80 bar
X / Y / Z	60 (2.36) / ± 1.5 (± 0.06) / 30 (1.18) mm (")



10085291 Drilling tool holder


Fixation	W serration
Mounting	Hydraulic expansion chuck D20
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	70 (2.76) / - / 48 (1.89) mm (")

Stationary tool holder Shank VDI25




10038299 Drilling tool holder

Fixation	W serration
Mounting	INDEX TRAUB CAPTO C3
Cooling	internal, p_{\max} 80 bar
X / Y / Z	70 (2.76) / - / -5 (-0.20) mm (")




10705777 Drilling tool holder

Fixation	W serration
Mounting	INDEX TRAUB CAPTO C3
Cooling	internal, p_{\max} 80 bar
X / Y / Z	70 (2.76) / - / 5 (0.20) mm (")




10593252 Turning tool holder, Form C1/C4

Fixation	none
Mounting	square 16x16
Cooling	external, p_{\max} 20 bar
X / Y / Z	55 (2.17) / - / 19 (0.75) mm (")




11033174 Turning tool holder, Form C2/C3

Fixation	none
Mounting	square 16x16
Cooling	external, p_{\max} 20 bar
X / Y / Z	55 (2.17) / - / 19 (0.75) mm (")




10199711 Turning tool holder, double

Fixation	none
Mounting	square 20x20
Cooling	external, p_{\max} 20 bar
X / Y / Z	55 (2.17) / - / 17 (0.67) mm (")




10443801 Turning tool holder, Form C1/C4

Fixation	none
Mounting	square 20x20
Cooling	external, p_{\max} 20 bar
X / Y / Z	55 (2.17) / - / 15 (0.59) mm (")




10940870 Turning tool holder, Form C2/C3

Fixation	none
Mounting	square 20x20
Cooling	external, p_{\max} 20 bar
X / Y / Z	55 (2.17) / - / 19 (0.75) mm (")




10252236 Turning tool holder, Form C2/C3

Fixation W serration
Mounting square 20x20
Cooling external, p_{\max} 20 bar
X / Y / Z 55 (2.17) / – / 19 (0.75) mm (")




10326998 Turning tool holder, Form C1/C4

Fixation W serration
Mounting square 20x20
Cooling external and internal, p_{\max} 80 bar
X / Y / Z 55 (2.17) / – / 15 (0.59) mm (")




10583476 Turning tool holder, Form C1/C4

Fixation W serration
Mounting square 20x20
Cooling external, p_{\max} 20 bar
X / Y / Z 55 (2.17) / – / 15 (0.59) mm (")




11095063 Turning tool holder, Form C2/C3

Fixation W serration
Mounting square 20x20
Cooling external and internal, p_{\max} 80 bar
X / Y / Z 55 (2.17) / – / 19 (0.75) mm (")




10345003 Turning tool holder, Form C1/C4

Fixation none
Mounting square 3/4x3/4"
Cooling external, p_{\max} 20 bar
X / Y / Z 55 (2.17) / – / 15 (0.59) mm (")



11064321 Turning tool holder, Form C2/C3


Fixation none
Mounting square 3/4x3/4"
Cooling external, p_{\max} 20 bar
X / Y / Z 55 (2.17) / – / 19 (0.75) mm (")



10042128 Turning tool holder, Form C2/C3


Fixation W serration
Mounting square 3/4x3/4"
Cooling external, p_{\max} 20 bar
X / Y / Z 55 (2.17) / – / 19 (0.75) mm (")

Stationary tool holder Shank VDI25




10295890 Turning tool holder, Form C1/C4

Fixation	W serration
Mounting	square 3/4x3/4"
Cooling	external, p_{\max} 20 bar
X / Y / Z	55 (2.17) / - / 15 (0.59) mm (")




10385115 Turning tool holder

Fixation	Clamping and stop bar
Mounting	square 20x20
Cooling	external, p_{\max} 80 bar
X / Y / Z	40 (1.57) / - / 30 (1.18) mm (")




10169442 Turning tool holder

Fixation	W serration
Mounting	square 20x20
Cooling	external, p_{\max} 20 bar
X / Y / Z	60 (2.36) / - / 30 (1.18) mm (")




10578028 Turning tool holder

Fixation	Vee bar
Mounting	square 20x20
Cooling	external, p_{\max} 80 bar
X / Y / Z	60 (2.36) / - / 30 (1.18) mm (")




10653020 Turning tool holder

Fixation	Vee bar
Mounting	square 20x20
Cooling	external, p_{\max} 80 bar
X / Y / Z	18.5 (0.73) / - / 30 (1.18) mm (")




10222400 Grooving tool holder

Fixation	W serration
Mounting	Trapezoid 32x4
Cooling	external, p_{\max} 20 bar
X / Y / Z	68.2 (2.69) / - / 30 (1.18) mm (")




10304690 Grooving tool holder

Fixation	W serration
Mounting	Trapezoid 32x4
Cooling	external, p_{\max} 20 bar
X / Y / Z	68.2 (2.69) / - / 30 (1.18) mm (")




10758898 Basic holder, Contour plunging tool holder

Fixation	W serration
Mounting	–
Cooling	external, p_{\max} 20 bar
X / Y / Z	28.3 (1.11) / – / – mm (")




10463581 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	–
Cooling	external, p_{\max} 20 bar
X / Y / Z	38 (1.50) / – / – mm (")




10607061 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	–
Cooling	external, p_{\max} 20 bar
X / Y / Z	30 (1.18) / – / – mm (")




10266235 Basic holder, vertically adjustable

Fixation	W serration
Mounting	–
Cooling	external, p_{\max} 20 bar
X / Y / Z	19 (0.75) / – / – mm (")




11094517 Stechhaltestück, vertikal einstellbar

Fixierung	–
Aufnahme	Trapez 26x4
Kühlung	außen und innen, p_{\max} 80 bar
X / Y / Z	63 / $\pm 1,5$ / 58 mm (")




10498677 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x4
Cooling	external, p_{\max} 20 bar
X / Y / Z	63 (2.48) / ± 1.5 (± 0.06) / 58 (2.28) mm (")




10668867 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x4
Cooling	external, p_{\max} 20 bar
X / Y / Z	63 (2.48) / ± 1.5 (± 0.06) / 58 (2.28) mm (")




11094518 Stechhaltestück, vertikal einstellbar

Fixierung	–
Aufnahme	Trapez 26x4
Kühlung	außen und innen, p_{\max} 80 bar
X / Y / Z	63 / $\pm 1,5$ / 58 mm (")




10804363 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x4
Cooling	external, p_{\max} 20 bar
X / Y / Z	63 (2.48) / ± 1.5 (± 0.06) / 58 (2.28) mm (")




10743913 Basic holder, horizontally adjustable

Fixation	W serration
Mounting	–
Cooling	external and internal, p_{\max} 20 bar
X / Y / Z	19.6 (0.77) / – / 30 (1.18) mm (")




10451779 Grooving tool holding block, horizontally adjustable

Fixation	–
Mounting	Trapezoid 32x3
Cooling	external, p_{\max} 20 bar
X / Y / Z	62 (2.44) / – / 19 (0.75) mm (")




10634677 Grooving tool holding block, horizontally adjustable

Fixation	–
Mounting	Trapezoid 32x3
Cooling	external, p_{\max} 20 bar
X / Y / Z	62 (2.44) / – / 19 (0.75) mm (")




10154506 Grooving tool holding block, horizontally adjustable

Fixation	–
Mounting	Trapezoid 32x3
Cooling	–, p_{\max} 20 bar
X / Y / Z	62 (2.44) / – / 33 (1.30) mm (")




10532047 Grooving tool holding block, horizontally adjustable

Fixation	–
Mounting	Trapezoid 32x3
Cooling	–, p_{\max} 20 bar
X / Y / Z	62 (2.44) / – / 30 (1.18) mm (")




10807382 Basic holder, vertically adjustable

Fixation	W serration
Mounting	–
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	35 (1.38) / – / 5 (0.20) mm (")




10928593 Basic holder, vertically adjustable

Fixation	Vee bar
Mounting	–
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	35 (1.38) / – / 5 (0.20) mm (")




10331903 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	square 16x10
Cooling	–
X / Y / Z	20 (0.79) / – / 18 (0.71) mm (")




10770991 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	square 16x16
Cooling	–
X / Y / Z	20 (0.79) / – / 17 (0.67) mm (")




11004141 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	square 16x16
Cooling	–
X / Y / Z	40 (1.57) / – / 40 (1.57) mm (")




10531179 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 16x3
Cooling	–
X / Y / Z	20 (0.79) / – / 25 (0.98) mm (")




10518257 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 20x4
Cooling	–
X / Y / Z	20 (0.79) / – / 25 (0.98) mm (")




10227285 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	20 (0.79) / – / 32 (1.26) mm (")




10049220 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	47.5 (1.87) / – / 32 (1.26) mm (")




10787914 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	47.5 (1.87) / – / 28.5 (1.12) mm (")




10410270 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	47.5 (1.87) / – / 32 (1.26) mm (")




10777825 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	47.5 (1.87) / – / 28.5 (1.12) mm (")




10269671 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 32x5
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	60 (2.36) / – / 32 (1.26) mm (")




10778011 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 32x5
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	60 (2.36) / – / 32 (1.26) mm (")




10500323 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 32x5
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	60 (2.36) / – / 32 (1.26) mm (")




11026512 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 32x5
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	60 (2.36) / – / 32 (1.26) mm (")




10442459 Knurling tool holding block

Fixation	none
Mounting	D6 (0.24 ")
Cooling	–
X / Y / Z	38 (1.50) / – / 20 (0.79) mm (")




10884330 Basic holder

Fixation	W serration
Mounting	–
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	78 (3.07) / – / -23.5 (-0.93) mm (")




10339021 Drill holding block

Fixation	none
Mounting	Hydraulic expansion chuck D12
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	77.5 (3.05) / – / – mm (")




10090979 Drill holding block

Fixation	none
Mounting	Hydraulic expansion chuck D20
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	83 (3.27) / – / – mm (")




10448204 Basic holder

Fixation	Vee bar
Mounting	–
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	70 (2.76) / – / -5 (-0.20) mm (")




10285739 Drill holding block

Fixation	–
Mounting	ER 25
Cooling	internal, p_{\max} 20 bar
X / Y / Z	42.5 (1.67) / – / – mm (")




10099852 Drill holding block

Fixation	–
Mounting	D20 (0.79 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	40 (1.57) / – / – mm (")




10030527 Center holder, vertically adjustable, not spring-loaded

Fixation	W serration
Mounting	D15.4 (0.61 ") / Cone 1:7.5
Cooling	external, p_{\max} 20 bar
X / Y / Z	70 (2.76) / ± 0.5 (± 0.02) / 46.5 (1.83) mm (")




10044237 Center holder, vertically adjustable, spring-loaded

Fixation	W serration
Mounting	D15.4 (0.61 ") / Cone 1:7.5
Cooling	external, p_{\max} 20 bar
X / Y / Z	70 (2.76) / ± 0.5 (± 0.02) / 46.5 (1.83) mm (")




10578860 Embossing roll holder

Fixation	none
Mounting	–
Cooling	internal, p_{\max} 20 bar
X / Y / Z	65 (2.56) / – / 40.5 (1.59) mm (")



10550535 Closing tool holder


Fixation	W serration
Mounting	D25 (0.98 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	65 (2.56) / – / 36.5 (1.44) mm (")



10880480 Calibrating tool


Fixation	none
Mounting	–
Cooling	–
X / Y / Z	110 (4.33) / – / – mm (")

Stationary tool holder Shank VDI25




10970015 Coolant nozzle

Fixation	none
Mounting	–
Cooling	–
X / Y / Z	16 (0.63) / – / – mm (")




10396777 Blanking plug

Fixation	–
Mounting	–
Cooling	–
X / Y / Z	10 (0.39) / – / – mm (")




10348092 Drilling unit

Fixation	W serration
Mounting	ER 11
Cooling	external, p_{\max} 80 bar
Speed ratio	1:3 (0.333)
X / Y / Z	75 (2.95) / – / 15 (0.59) mm (")




10271046 Drilling unit

Fixation	Vee bar
Mounting	ER 11
Cooling	external, p_{\max} 20 bar
Speed ratio	1:3 (0.333)
X / Y / Z	75 (2.95) / – / 15 (0.59) mm (")




10077056 Drilling unit

Fixation	Vee bar
Mounting	ER 11
Cooling	external, p_{\max} 20 bar
Speed ratio	1:1.33 (0.75)
X / Y / Z	70 (2.76) / – / 17.5 (0.69) mm (")




10152559 Drilling unit, vertically adjustable

Fixation	W serration
Mounting	ER 16
Cooling	external, p_{\max} 20 bar
Speed ratio	1:2.07 (0.483)
X / Y / Z	85 (3.35) / ± 22.5 (± 0.98) / 22.5 (0.89) mm (")




11029935 Drilling unit

Fixation	none
Mounting	ER 20
Cooling	external, p_{\max} 40 bar
Speed ratio	1:1 (1)
X / Y / Z	54 (2.13) / – / 0 () mm (")




10151509 Milling unit

Fixation	none
Mounting	DIN 1835 B/E D16 (0.63 ")
Cooling	external, p_{\max} 40 bar
Speed ratio	1:1 (1)
X / Y / Z	84 (3.31) / – / 0 () mm (")




10967728 Milling unit

Fixation	none
Mounting	D16 (0.63 ")
Cooling	external, p_{\max} 40 bar
Speed ratio	4.5:1 (4.5)
X / Y / Z	82 (3.23) / – / 0 () mm (")




10266335 Tapping unit, extendable

Fixation	none
Mounting	ER 20
Cooling	external, p_{\max} 40 bar
Speed ratio	1:1 (1)
X / Y / Z	60 (2.36) / - / 0 () mm (")




10242122 Circular saw unit

Fixation	Vee bar
Mounting	Milling shaft D16 (0.63 ")
Cooling	external, p_{\max} 40 bar
Speed ratio	2,7:1 (2,7)
X / Y / Z	68 (2.68) / - / 0 () mm (")




10198915 Circular saw unit

Fixation	W serration
Mounting	Milling shaft D16 (0.63 ")
Cooling	external, p_{\max} 80 bar
Speed ratio	2.9:1 (2.9)
X / Y / Z	74 (2.91) / - / - mm (")




10420364 Drilling unit

Fixation	W serration
Mounting	ER 16
Cooling	external, internal optional, p_{\max} 80 bar
Speed ratio	1:2 (0.5)
X / Y / Z	70 (2.76) / - / 80 (3.15) mm (")




10090413 Milling unit

Fixation	W serration
Mounting	ER 25
Cooling	external, internal optional, p_{\max} 80 bar
Speed ratio	1:1 (1)
X / Y / Z	60 (2.36) / - / 64 (2.52) mm (")



10174204 Milling unit


Fixation	W serration
Mounting	ER 25
Cooling	external, internal optional, p_{\max} 80 bar
Speed ratio	1:1 (1)
X / Y / Z	70 (2.76) / - / 64 (2.52) mm (")



10223315 Milling unit


Fixation	Vee bar
Mounting	ER 25
Cooling	external, internal optional, p_{\max} 80 bar
Speed ratio	1:1 (1)
X / Y / Z	70 (2.76) / - / 64 (2.52) mm (")

Live tool holder Shank VDI25




10771991 Milling unit

Fixation	Vee bar
Mounting	ER 25
Cooling	external, internal optional, p_{\max} 80 bar
Speed ratio	1:1 (1)
X / Y / Z	60 (2.36) / – / 64 (2.52) mm (")




10803114 Milling unit

Fixation	W serration
Mounting	ER 25
Cooling	external, internal optional, p_{\max} 80 bar
Speed ratio	2:1 (2)
X / Y / Z	70 (2.76) / – / 64 (2.52) mm (")




10886532 Milling unit

Fixation	Vee bar
Mounting	ER 25
Cooling	external, internal optional, p_{\max} 80 bar
Speed ratio	2:1 (2)
X / Y / Z	70 (2.76) / – / 64 (2.52) mm (")




10780758 Milling unit

Fixation	Vee bar
Mounting	Milling shaft D16 (0.63 ")
Cooling	external, p_{\max} 40 bar
Speed ratio	2.09:1 (2.09)
X / Y / Z	55 (2.17) / – / 47.5 (1.87) mm (")




10309286 Milling unit

Fixation	W serration
Mounting	Milling shaft D16 (0.63 ")
Cooling	external, p_{\max} 80 bar
Speed ratio	2.5:1 (2.5)
X / Y / Z	55 (2.17) / – / 45 (1.77) mm (")




10004506 Milling unit

Fixation	W serration
Mounting	–
Cooling	external, p_{\max} 80 bar
Speed ratio	2.5:1 (2.5)
X / Y / Z	55 (2.17) / – / 53 (2.09) mm (")




10765304 Milling unit

Fixation	Vee bar
Mounting	–
Cooling	external, p_{\max} 80 bar
Speed ratio	2.5:1 (2.5)
X / Y / Z	55 (2.17) / – / 53 (2.09) mm (")




10670447 Milling cutter holding block

Fixation	–
Mounting	Milling shaft D13 (0.51 ")
Cooling	–
X / Y / Z	– / – / – mm (")




11041286 Milling cutter holding block

Fixation	–
Mounting	Milling shaft D16 (0.63 ")
Cooling	–
X / Y / Z	– / – / – mm (")




10435497 Milling cutter holding block

Fixation	–
Mounting	Milling shaft D22 (0.87 ")
Cooling	–
X / Y / Z	– / – / – mm (")




12011567 Milling cutter holding block

Fixation	–
Mounting	Milling shaft D22 (0.87 ")
Cooling	–
X / Y / Z	32.5 (1.28) / – / – mm (")




10807705 Milling cutter holding block

Fixation	–
Mounting	Milling shaft D27 (1.06 ")
Cooling	–
X / Y / Z	– / – / – mm (")




10223928 Milling cutter holding block

Fixation	–
Mounting	Milling shaft D32 (1.26 ")
Cooling	–
X / Y / Z	– / – / – mm (")




10397223 Tapping unit, extendable

Fixation	Clamping and stop bar
Mounting	ER 20
Cooling	external, p _{max} 40 bar
Speed ratio	2:1 (2)
X / Y / Z	70 (2.76) / – / 78 (3.07) mm (")




10414768 Broaching/ Slotting unit

Fixation	W serration
Mounting	D20 (0.79 ")
Cooling	external and internal, p_{\max} 80 bar
Speed ratio	1:1 (1)
X / Y / Z	60 (2.36) / – / 69 (2.72) mm (")




10750447 Broaching/ Slotting unit

Fixation	Vee bar
Mounting	D20 (0.79 ")
Cooling	external, internal optional, p_{\max} 80 bar
Speed ratio	1:1 (1)
X / Y / Z	60 (2.36) / – / 69 (2.72) mm (")



10798991 Drilling unit, angle-adjustable


Fixation	W serration
Mounting	ER 11
Cooling	external, p_{\max} 80 bar
Speed ratio	1:1.7 (0.588)
X / Y / Z	44 (1.73) / – / 37 (1.46) mm (")



10465360 Drilling unit, angle-adjustable


Fixation	Vee bar
Mounting	ER 11
Cooling	external, p_{\max} 80 bar
Speed ratio	1:1.7 (0.588)
X / Y / Z	44 (1.73) / – / 67 (2.64) mm (")

Tool holder to spring-loaded tap holder Shank VDI20




10979044 Bar stop, adjustable, live

Fixation	none
Mounting	–
Cooling	–
X / Y / Z	49.5 - 71.5 (1.95 - 2.81) / – / – mm (")




10592190 Drilling tool holder

Fixation	none
Mounting	ER 16
Cooling	internal, p_{\max} 20 bar
X / Y / Z	42.5 (1.67) / – / – mm (")




10620002 Drilling tool holder, Form E4

Fixation	none
Mounting	ER 25
Cooling	internal, p_{\max} 80 bar
X / Y / Z	51 (2.01) / – / – mm (")




10980163 Drilling tool holder, Form E4

Fixation	none
Mounting	ER 40
Cooling	internal, p_{\max} 20 bar
X / Y / Z	66.5 (2.62) / – / – mm (")




10359056 Drilling tool holder, Form E1

Fixation	none
Mounting	DIN 1835 B/E D20 (0.79 ")
Cooling	internal, p_{\max} 20 bar
X / Y / Z	48 (1.89) / – / – mm (")




10880044 Drilling tool holder, Form E1

Fixation	none
Mounting	DIN 1835 B/E D25 (0.98 ")
Cooling	internal, p_{\max} 80 bar
X / Y / Z	56.5 (2.22) / – / – mm (")




10879047 Drilling tool holder, Form E2

Fixation	none
Mounting	D10 (0.39 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	50 (1.97) / – / – mm (")




10367178 Drilling tool holder, Form E2

Fixation	none
Mounting	D12 (0.47 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	50 (1.97) / - / - mm (")




10271806 Drilling tool holder

Fixation	none
Mounting	D15 (0.59 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	26 (1.02) / - / - mm (")




10630888 Drilling tool holder, Form E2

Fixation	none
Mounting	D16 (0.63 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	50 (1.97) / - / - mm (")




10270233 Drilling tool holder

Fixation	none
Mounting	D25 (0.98 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	43 (1.69) / - / - mm (")




10711364 Basic holder, vertically adjustable

Fixation	none
Mounting	-
Cooling	internal, p_{\max} 20 bar
X / Y / Z	14 (0.55) / - / - mm (")



10285739 Drill holding block


Fixation	-
Mounting	ER 25
Cooling	internal, p_{\max} 20 bar
X / Y / Z	42.5 (1.67) / - / - mm (")



10099852 Drill holding block


Fixation	-
Mounting	D20 (0.79 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	40 (1.57) / - / - mm (")

Tool holder to spring-loaded tap holder Shank VDI20




11042772 Center holder, elastic, live, Center replaceble

Fixation	none
Mounting	MK0
Cooling	–
X / Y / Z	66 (2.60) / – / – mm (")




110573888 Center holder, elastic, live

Fixation	none
Mounting	–
Cooling	–
X / Y / Z	65 (2.56) / – / – mm (")




11041774 Tapping tool holder, over-running

Fixation	none
Mounting	D12 (0.47 ")
Cooling	external, p _{max} 20 bar
X / Y / Z	56 (2.20) / – / – mm (")




10010548 Tapping tool holder

Fixation	none
Mounting	D18 (0.71 ")
Cooling	external, p _{max} 20 bar
X / Y / Z	50.5 (1.99) / – / – mm (")




10078189 Reaming tool holder, adjustable

Fixation	none
Mounting	D12 (0.47 ")
Cooling	external, p _{max} 20 bar
X / Y / Z	52 (2.05) / – / – mm (")



10061447 Broaching/ Slotting holder, rotating, live


Fixation	none
Mounting	D12 (0.47 ")
Cooling	external, p _{max} 20 bar
X / Y / Z	66 (2.60) / – / – mm (")



10548417 Broaching/ Slotting holder, rotating, live


Fixation	none
Mounting	D24 (0.94 ")
Cooling	external, p _{max} 20 bar
X / Y / Z	69 (2.72) / – / – mm (")

Tool holder to spring-loaded tap holder Shank VDI25




10027773 Drilling tool holder, Form E4

Fixation	none
Mounting	ER 25
Cooling	internal, p_{max} 40 bar
X / Y / Z	57 (2.24) / - / - mm (")




10406859 Drilling tool holder, Form E4

Fixation	none
Mounting	ER 32
Cooling	internal, p_{max} 80 bar
X / Y / Z	62 (2.44) / - / - mm (")




10882358 Drilling tool holder, Form E1

Fixation	none
Mounting	DIN 1835 B/E D16 (0.63 ")
Cooling	internal, p_{max} 80 bar
X / Y / Z	67 (2.64) / - / - mm (")




10003339 Drilling tool holder, Form E1

Fixation	none
Mounting	DIN 1835 B/E D20 (0.79 ")
Cooling	internal, p_{max} 80 bar
X / Y / Z	67 (2.64) / - / - mm (")




10340141 Drilling tool holder, Form E1

Fixation	none
Mounting	DIN 1835 B/E D25 (0.98 ")
Cooling	internal, p_{max} 80 bar
X / Y / Z	71 (2.80) / - / - mm (")



10919291 Drilling tool holder, Form E1


Fixation	none
Mounting	DIN 1835 B/E D32 (1.26 ")
Cooling	internal, p_{max} 80 bar
X / Y / Z	74 (2.91) / - / - mm (")



10058371 Drilling tool holder, Form E2


Fixation	none
Mounting	D8 (0.31 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")

Tool holder to spring-loaded tap holder Shank VDI25




10503585 Drilling tool holder, Form E2

Fixation	none
Mounting	D10 (0.39 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")




10773801 Drilling tool holder, Specially for the marking tool WriteStar

Fixation	none
Mounting	D12 (0.47 ")
Cooling	-
X / Y / Z	68 (2.68) / - / - mm (")




10983815 Drilling tool holder, Form E2

Fixation	none
Mounting	D12 (0.47 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")




10471993 Drilling tool holder, Form E2

Fixation	none
Mounting	D16 (0.63 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")




10749389 Drilling tool holder, Form E2

Fixation	none
Mounting	D20 (0.79 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")



10329247 Drilling tool holder, Form E2


Fixation	none
Mounting	D25 (0.98 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	60 (2.36) / - / - mm (")



10208692 Compensation bushing


Fixation	none
Mounting	D3/4"
Cooling	-
X / Y / Z	6 (0.24) / - / - mm (")

Tool holder to spring-loaded tap holder Shank VDI25




10467520 Tapping tool holder, extendable

Fixation	none
Mounting	DIN 1835 B/E D18 (0.71 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	50 (1.97) / - / - mm (")




10365449 Reaming tool holder

Fixation	none
Mounting	ER 25
Cooling	internal, p_{\max} 20 bar
X / Y / Z	61 (2.40) / - / - mm (")



10252714 Broaching/ Slotting holder, rotating, live


Fixation	none
Mounting	D12 (0.47 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	60 (2.36) / - / - mm (")



10489412 Calibrating tool


Fixation	none
Mounting	-
Cooling	-
X / Y / Z	190 (7.48) / - / - mm (")

Tool holder to spring-loaded tap holder Shank VDI30




10428174 Bar stop, adjustable, live

Fixation	none
Mounting	–
Cooling	–
X / Y / Z	60 - 97 (2.36 - 3.82) / – / – mm (")




10679593 Bar stop, adjustable, live

Fixation	none
Mounting	–
Cooling	–
X / Y / Z	60 - 97 (2.36 - 3.82) / – / – mm (")




10424888 Drilling tool holder, Form E4

Fixation	none
Mounting	ER 25
Cooling	internal, p_{max} 80 bar
X / Y / Z	68 (2.68) / – / – mm (")




10453838 Drilling tool holder, Form E4

Fixation	none
Mounting	ER 32
Cooling	internal, p_{max} 20 bar
X / Y / Z	76 (2.99) / – / – mm (")




10239645 Drilling tool holder, Form E4

Fixation	none
Mounting	ER 40
Cooling	internal, p_{max} 80 bar
X / Y / Z	80 (3.15) / – / – mm (")



10502799 Drilling tool holder, Form E1


Fixation	none
Mounting	DIN 1835 E D20 (0.79 ")
Cooling	internal, p_{max} 80 bar
X / Y / Z	67 (2.64) / – / – mm (")



10659026 Drilling tool holder, Form E1


Fixation	none
Mounting	DIN 1835 E D25 (0.98 ")
Cooling	internal, p_{max} 80 bar
X / Y / Z	71 (2.80) / – / – mm (")

Tool holder to spring-loaded tap holder Shank VDI30




10168049 Drilling tool holder, Form E2

Fixation	none
Mounting	D8 (0.31 ")
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	60 (2.36) / - / - mm (")




10364335 Drilling tool holder, Form E2

Fixation	none
Mounting	D10 (0.39 ")
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	60 (2.36) / - / - mm (")




10240059 Drilling tool holder, Form E2

Fixation	none
Mounting	D12 (0.47 ")
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	60 (2.36) / - / - mm (")




11043672 Drilling tool holder, Specially for the marking tool WriteStar

Fixation	none
Mounting	D12 (0.47 ")
Cooling	-
X / Y / Z	68 (2.68) / - / - mm (")




10298106 Drilling tool holder, Form E2

Fixation	none
Mounting	D16 (0.63 ")
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	60 (2.36) / - / - mm (")



10806859 Drilling tool holder, Form E2


Fixation	none
Mounting	D20 (0.79 ")
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	60 (2.36) / - / - mm (")



10040148 Drilling tool holder


Fixation	none
Mounting	D25 (0.98 ")
Cooling	external and internal, p_{max} 40 bar
X / Y / Z	45 (1.77) / - / - mm (")

Tool holder to spring-loaded tap holder Shank VDI30




10175060 Drilling tool holder, Form E2

Fixation	none
Mounting	D25 (0.98 ")
Cooling	external and internal, p_{\max} 20 bar
X / Y / Z	60 (2.36) / - / - mm (")




10601688 Drilling tool holder

Fixation	none
Mounting	D32 (1.26 ")
Cooling	internal, p_{\max} 80 bar
X / Y / Z	73 (2.87) / - / - mm (")




11055569 Drilling tool holder, Form E2

Fixation	none
Mounting	D32 (1.26 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	70 (2.76) / - / - mm (")




10631335 Drilling tool holder

Fixation	none
Mounting	MK1
Cooling	external, p_{\max} 20 bar
X / Y / Z	30 (1.18) / - / - mm (")




10550804 Drilling tool holder

Fixation	none
Mounting	MK2
Cooling	external, p_{\max} 20 bar
X / Y / Z	27 (1.06) / - / - mm (")



10677499 Drilling tool holder


Fixation	none
Mounting	MK3
Cooling	external, p_{\max} 20 bar
X / Y / Z	45 (1.77) / - / - mm (")



10921732 Compensation bushing


Fixation	none
Mounting	D3/4"
Cooling	-
X / Y / Z	6 (0.24) / - / - mm (")

Tool holder to spring-loaded tap holder Shank VDI30




11033529 Compensation bushing

Fixation	none
Mounting	D1"
Cooling	–
X / Y / Z	6 (0.24) / – / – mm (")




10217247 Basic holder, vertically adjustable

Fixation	none
Mounting	–
Cooling	external, p_{\max} 20 bar
X / Y / Z	14 (0.55) / – / – mm (")




10374519 Drill holding block

Fixation	–
Mounting	ER 25
Cooling	–, p_{\max} 40 bar
X / Y / Z	30 (1.18) / – / – mm (")




10193528 Drill holding block

Fixation	–
Mounting	D32 (1.26 ")
Cooling	–, p_{\max} 40 bar
X / Y / Z	57 (2.24) / – / – mm (")




10387522 Center holder, elastic, live

Fixation	none
Mounting	D15.4 (0.61 ") / Cone 1:7.5
Cooling	–
X / Y / Z	68.5 (2.70) / – / – mm (")



10593935 Center holder, live


Fixation	none
Mounting	D15.4 (0.61 ") / Cone 1:7.5
Cooling	–
X / Y / Z	69.5 (2.74) / – / – mm (")



10301384 Tapping tool holder, extendable


Fixation	none
Mounting	D25 (0.98 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	73 (2.87) / – / – mm (")

Tool holder to spring-loaded tap holder Shank VDI30




10894326 Reaming tool holder, adjustable

Fixation	none
Mounting	ER 25
Cooling	external, p_{\max} 20 bar
X / Y / Z	73.5 (2.89) / - / - mm (")




11041243 Reaming tool holder, adjustable

Fixation	none
Mounting	D18 (0.71 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	59 (2.32) / - / - mm (")



10459517 Reaming tool holder, self-centering


Fixation	none
Mounting	D20 (0.79 ")
Cooling	internal, p_{\max} 40 bar
X / Y / Z	93 (3.66) / - / - mm (")



10929722 Broaching/ Slotting holder, rotating, live


Fixation	none
Mounting	D12 (0.47 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	60 (2.36) / - / - mm (")

Stationary tool holder Vee mounting




10677834 Bar stop, adjustable

Fixation	none
Mounting	–
Cooling	–
X / Y / Z	85 (3.35) / – / -17 (-0.67) mm (")




10631691 Turning tool holder, double

Fixation	none
Mounting	square 20x20
Cooling	external, p _{max} 20 bar
X / Y / Z	65 (2.56) / – / 0 () mm (")




10665762 Turning tool holder

Fixation	none
Mounting	square 20x20
Cooling	external, p _{max} 20 bar
X / Y / Z	85 (3.35) / – / 0 () mm (")




10160728 Basic holder, adjustable

Fixation	none
Mounting	–
Cooling	external, p _{max} 40 bar
X / Y / Z	52 (2.05) / – / 10 (0.39) mm (")




10331903 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	square 16x10
Cooling	–
X / Y / Z	20 (0.79) / – / 18 (0.71) mm (")



10770991 Grooving tool holding block, vertically adjustable


Fixation	–
Mounting	square 16x16
Cooling	–
X / Y / Z	20 (0.79) / – / 17 (0.67) mm (")



11004141 Grooving tool holding block, vertically adjustable


Fixation	–
Mounting	square 16x16
Cooling	–
X / Y / Z	40 (1.57) / – / 40 (1.57) mm (")

Stationary tool holder Vee mounting




10799021 Grooving tool holding block, adjustable

Fixation	–
Mounting	square 20x20
Cooling	–
X / Y / Z	37 (1.46) / – / 28 (1.10) mm (")




10976603 Grooving tool holding block, adjustable

Fixation	–
Mounting	square 20x20
Cooling	–
X / Y / Z	45 (1.77) / – / 28 (1.10) mm (")




10531179 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 16x3
Cooling	–
X / Y / Z	20 (0.79) / – / 25 (0.98) mm (")




10518257 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 20x4
Cooling	–
X / Y / Z	20 (0.79) / – / 25 (0.98) mm (")




10227285 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	20 (0.79) / – / 32 (1.26) mm (")



10049220 Grooving tool holding block, vertically adjustable


Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	47.5 (1.87) / – / 32 (1.26) mm (")



10787914 Grooving tool holding block, vertically adjustable


Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	47.5 (1.87) / – / 28.5 (1.12) mm (")

Stationary tool holder Vee mounting




10410270 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	47.5 (1.87) / – / 32 (1.26) mm (")




10777825 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	Trapezoid 26x5
Cooling	–
X / Y / Z	47.5 (1.87) / – / 28.5 (1.12) mm (")




10442459 Knurling tool holding block

Fixation	none
Mounting	D6 (0.24 ")
Cooling	–
X / Y / Z	38 (1.50) / – / 20 (0.79) mm (")




10792715 Basic holder, angle-adjustable

Fixation	none
Mounting	–
Cooling	external, p _{max} 40 bar
X / Y / Z	42 (1.65) / – / 0 () mm (")




10607061 Grooving tool holding block, vertically adjustable

Fixation	–
Mounting	–
Cooling	external, p _{max} 20 bar
X / Y / Z	30 (1.18) / – / – mm (")



10463581 Grooving tool holding block, vertically adjustable


Fixation	–
Mounting	–
Cooling	external, p _{max} 20 bar
X / Y / Z	38 (1.50) / – / – mm (")



10915096 Basic holder, Contour plunging tool holder


Fixation	none
Mounting	–
Cooling	external, p _{max} 40 bar
X / Y / Z	45.5 (1.79) / – / 9 (0.35) mm (")

Stationary tool holder Vee mounting




10170595 Grooving tool holding block, adjustable

Fixation	–
Mounting	–
Cooling	–
X / Y / Z	40 (1.57) / – / – mm (")




10463891 Basic holder, vertically adjustable

Fixation	none
Mounting	–
Cooling	external and internal, p_{max} 20 bar
X / Y / Z	62 (2.44) / – / -30 (-1.18) mm (")




10159310 Drill holding block

Fixation	–
Mounting	D25 (0.98 ")
Cooling	internal, p_{max} 20 bar
X / Y / Z	23.55 (0.93) / – / – mm (")




10065358 Drill holding block

Fixation	none
Mounting	D25 (0.98 ")
Cooling	internal, p_{max} 20 bar
X / Y / Z	33.55 (1.32) / – / 50 (1.97) mm (")




10935806 Drill holding block, horizontally adjustable

Fixation	–
Mounting	D1"
Cooling	internal, p_{max} 20 bar
X / Y / Z	23.55 (0.93) / – / 50 (1.97) mm (")



10854446 Center holder, elastic


Fixation	–
Mounting	MK1
Cooling	–
X / Y / Z	85 (3.35) / – / -71 (-2.80) mm (")



10175570 Embossing roll holder


Fixation	–
Mounting	–
Cooling	–, p_{max} 40 bar
X / Y / Z	90 (3.54) / – / – mm (")

Stationary tool holder Vee mounting



11076016 Calibrating tool


Fixation	none
Mounting	D40 (1.57 ")
Cooling	–
X / Y / Z	110 (4.33) / – / 0 () mm (")



10215385 Cover plate, Steel


Fixation	none
Mounting	–
Cooling	–
X / Y / Z	12 (0.47) / – / – mm (")

Live tool holder Vee mounting




10274097 Drilling unit

Fixation	none
Mounting	ER 11
Cooling	external, p_{\max} 20 bar
Speed ratio	1:1.33 (0.75)
X / Y / Z	87 (3.43) / – / 1.5 (0.06) mm (")




10607059 Drilling unit, vertically adjustable

Fixation	none
Mounting	ER 16
Cooling	external, p_{\max} 20 bar
Speed ratio	1:1.93 (0.518)
X / Y / Z	105 (4.13) / – / 37.5 (1.48) mm (")




10817882 Drilling unit

Fixation	none
Mounting	ER 20
Cooling	external, p_{\max} 40 bar
Speed ratio	1:1 (1)
X / Y / Z	64 (2.52) / – / -16.5 (-0.65) mm (")




10622114 Milling unit

Fixation	none
Mounting	DIN 1835 B/E D16 (0.63 ")
Cooling	external, p_{\max} 40 bar
Speed ratio	4.5:1 (4.5)
X / Y / Z	96 (3.78) / – / -16.5 (-0.65) mm (")




11165932 Milling unit

Fixation	–
Mounting	Milling shaft D22 (0.87 ")
Cooling	external, p_{\max} 40 bar
Speed ratio	4.5:1 (4.5)
X / Y / Z	88 (3.46) / – / – mm (")



10130569 Drilling unit


Fixation	none
Mounting	ER 20
Cooling	external, p_{\max} 20 bar
Speed ratio	1:1.13 (0.8857)
X / Y / Z	85 (3.35) / – / 36.5 (1.44) mm (")



10760798 Drilling unit, angle-adjustable


Fixation	–
Mounting	ER 11
Cooling	external, p_{\max} 80 bar
Speed ratio	1:1.7 (0.588)
X / Y / Z	62 (2.44) / – / 37 (1.46) mm (")

Stationary tool holder Shank VDI25, Rear End Machining Unit




10027773 Drilling tool holder, Form E4

Fixation	none
Mounting	ER 25
Cooling	internal, p_{\max} 40 bar
X / Y / Z	57 (2.24) / - / - mm (")




10406859 Drilling tool holder, Form E4

Fixation	none
Mounting	ER 32
Cooling	internal, p_{\max} 80 bar
X / Y / Z	62 (2.44) / - / - mm (")




10882358 Drilling tool holder, Form E1

Fixation	none
Mounting	DIN 1835 B/E D16 (0.63 ")
Cooling	internal, p_{\max} 80 bar
X / Y / Z	67 (2.64) / - / - mm (")




10003339 Drilling tool holder, Form E1

Fixation	none
Mounting	DIN 1835 B/E D20 (0.79 ")
Cooling	internal, p_{\max} 80 bar
X / Y / Z	67 (2.64) / - / - mm (")




10340141 Drilling tool holder, Form E1

Fixation	none
Mounting	DIN 1835 B/E D25 (0.98 ")
Cooling	internal, p_{\max} 80 bar
X / Y / Z	71 (2.80) / - / - mm (")



10919291 Drilling tool holder, Form E1

Fixation	none
Mounting	DIN 1835 B/E D32 (1.26 ")
Cooling	internal, p_{\max} 80 bar
X / Y / Z	74 (2.91) / - / - mm (")




10058371 Drilling tool holder, Form E2

Fixation	none
Mounting	D8 (0.31 ")
Cooling	external and internal, p_{\max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")


Stationary tool holder Shank VDI25, Rear End Machining Unit

INDEX TRAUB




10503585 Drilling tool holder, Form E2

Fixation	none
Mounting	D10 (0.39 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")




10773801 Drilling tool holder, Specially for the marking tool WriteStar

Fixation	none
Mounting	D12 (0.47 ")
Cooling	-
X / Y / Z	68 (2.68) / - / - mm (")




10983815 Drilling tool holder, Form E2

Fixation	none
Mounting	D12 (0.47 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")




10471993 Drilling tool holder, Form E2

Fixation	none
Mounting	D16 (0.63 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")




10749389 Drilling tool holder, Form E2

Fixation	none
Mounting	D20 (0.79 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	50 (1.97) / - / - mm (")



10329247 Drilling tool holder, Form E2


Fixation	none
Mounting	D25 (0.98 ")
Cooling	external and internal, p_{max} 80 bar
X / Y / Z	60 (2.36) / - / - mm (")



10208692 Compensation bushing


Fixation	none
Mounting	D3/4"
Cooling	-
X / Y / Z	6 (0.24) / - / - mm (")

Stationary tool holder Shank VDI25, Rear End Machining Unit




10467520 Tapping tool holder, extendable

Fixation	none
Mounting	DIN 1835 B/E D18 (0.71 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	50 (1.97) / - / - mm (")




10365449 Reaming tool holder

Fixation	none
Mounting	ER 25
Cooling	internal, p_{\max} 20 bar
X / Y / Z	61 (2.40) / - / - mm (")



10252714 Broaching/ Slotting holder, rotating, live


Fixation	none
Mounting	D12 (0.47 ")
Cooling	external, p_{\max} 20 bar
X / Y / Z	60 (2.36) / - / - mm (")



10489412 Calibrating tool


Fixation	none
Mounting	-
Cooling	-
X / Y / Z	190 (7.48) / - / - mm (")

Live tool holder Shank VDI25, Rear End Machining Unit




10911974 Drilling unit

Fixation	none
Mounting	ER 20
Cooling	external, p_{\max} 40 bar
Speed ratio	1:1 (1)
X / Y / Z	54 (2.13) / - / 0 () mm (")



10787046 Tapping unit, extendable


Fixation	none
Mounting	ER 20
Cooling	external, p_{\max} 40 bar
Speed ratio	1:1 (1)
X / Y / Z	60 (2.36) / - / 0 () mm (")



10693707 Circular saw unit


Fixation	Vee bar
Mounting	Milling shaft D16 (0.63 ")
Cooling	external, p_{\max} 40 bar
Speed ratio	2,7:1 (2,7)
X / Y / Z	68 (2.68) / - / 0 () mm (")

Stationary tool holder Shank 1", Rear End Machining Unit




10709196 Drilling tool holder

Fixation	none
Mounting	ER 25
Cooling	internal, p_{max} 40 bar
X / Y / Z	50 (1.97) / - / 0 () mm (")




10884174 Drilling tool holder

Fixation	none
Mounting	ER 25
Cooling	-
X / Y / Z	22 (0.87) / - / - mm (")




10605788 Drilling tool holder

Fixation	none
Mounting	DIN 1835 B/E D25 (0.98 ")
Cooling	internal, p_{max} 40 bar
X / Y / Z	56 (2.20) / - / 0 () mm (")




10720434 Drilling tool holder, adjustable

Fixation	none
Mounting	D18 (0.71 ")
Cooling	internal, p_{max} 20 bar
X / Y / Z	56 (2.20) / ± 2 (± 0.08) / ± 2 (0.08) mm (")




10036301 Drilling tool holder

Fixation	none
Mounting	D25 (0.98 ")
Cooling	-
X / Y / Z	40 (1.57) / - / - mm (")



11061115 Drilling tool holder


Fixation	none
Mounting	MK1
Cooling	-
X / Y / Z	16 (0.63) / - / - mm (")



10083633 Drilling tool holder


Fixation	none
Mounting	MK2
Cooling	-
X / Y / Z	29 (1.14) / - / - mm (")

Stationary tool holder Shank 1", Rear End Machining Unit




10886503 Center holder, elastic, live

Fixation	none
Mounting	D18 (0.71 ")
Cooling	–
X / Y / Z	72.5 (2.85) / – / – mm (")




10816897 Center holder, elastic, live

Fixation	none
Mounting	MK1
Cooling	–
X / Y / Z	72.5 (2.85) / – / – mm (")




10390181 Tapping tool holder, over-running

Fixation	none
Mounting	D25 (0.98 ")
Cooling	–
X / Y / Z	56 (2.20) / – / – mm (")




10628055 Tapping tool holder, extendable

Fixation	none
Mounting	D25 (0.98 ")
Cooling	–
X / Y / Z	52 (2.05) / – / – mm (")




10631262 Reaming tool holder, adjustable

Fixation	none
Mounting	ER 25
Cooling	–
X / Y / Z	55 (2.17) / – / – mm (")



10448325 Reaming tool holder, adjustable


Fixation	none
Mounting	D18 (0.71 ")
Cooling	–
X / Y / Z	41 (1.61) / – / – mm (")



10826026 Broaching/ Slotting holder, rotating, live


Fixation	none
Mounting	D12 (0.47 ")
Cooling	–
X / Y / Z	58 (2.28) / – / – mm (")

Stationary tool holder Shank 1", Rear End Machining Unit




10913831 Broaching/ Slotting holder, rotating, live

Fixation	none
Mounting	D20 (0.79 ")
Cooling	–
X / Y / Z	76 (2.99) / – / – mm (")




10281269 Broaching/ Slotting holder, rotating, live

Fixation	none
Mounting	D40 (1.57 ")
Cooling	–
X / Y / Z	78 - 88 (3.07 - 3.46) / – / – mm (")




11062082 Broaching/ Slotting holder

Fixation	none
Mounting	D50 (1.97 ")
Cooling	–
X / Y / Z	80 - 90 (3.15 - 3.54) / – / – mm (")




10929225 Guide holder

Fixation	none
Mounting	–
Cooling	–
X / Y / Z	57 (2.24) / – / – mm (")




10665432 Roller holding block, adjustable

Fixation	–
Mounting	–
Cooling	–
X / Y / Z	– / – / – mm (")



11002956 Roller holding block, adjustable


Fixation	–
Mounting	–
Cooling	–
X / Y / Z	– / – / – mm (")



10722345 Knurling tool holder, adjustable


Fixation	none
Mounting	D6-36 (0.24 "-1.24 ")
Cooling	–
X / Y / Z	– / – / – mm (")

Live tool holder Shank 1", Rear End Machining Unit




10229360 Drilling unit

Fixation	none
Mounting	ER 25
Cooling	external, p_{\max} 40 bar
Speed ratio	1:1 (1)
X / Y / Z	68 (2.68) / - / 0 () mm (")



10717845 Tapping unit, extendable

Fixation	none
Mounting	ER 16
Cooling	external, p_{\max} 40 bar
Speed ratio	1:1 (1)
X / Y / Z	61 (2.40) / - / 0 () mm (")



10922705 Circular saw unit

Fixation	none
Mounting	Milling shaft D16 (0.63 ")
Cooling	external, p_{\max} 40 bar
Speed ratio	2,7:1 (2,7)
X / Y / Z	75 (2.95) / ± 12.5 (± 0.49) / 0 () mm (")



**INDEX-Werke GmbH & Co. KG
Hahn & Tessky**

Plochinger Straße 92
D-73730 Esslingen

Fon +49 711 3191-0
Fax +49 711 3191-587

info@index-werke.de
www.index-werke.de