

## Unscrewing device,42 mm

### Technical data

|                             |   |
|-----------------------------|---|
| <b>INDEX TRAUB products</b> | ABC • C100 • ABC.2  |
| <b>Function (Component)</b> | Unscrewing device   |
| <b>Spindle clearance</b>    | 42mm  |
| <b>Bar loading magazine</b> | INDEX MBL   |
| <b>Clamping stroke</b>      | 7mm (0.28") • 12.5mm (0.49")  |
| <b>Machining side</b>       | Main spindle  |
| <b>Material diameter</b>    | 5mm (0.20") • 6mm (0.24") • 7mm (0.28") • 8mm (0.31") • 9mm (0.35") • 10mm (0.39") • 11mm (0.43") • 12mm (0.47") • 13mm (0.51") • 14mm (0.55") • 15mm (0.59") • 16mm (0.63") • 17mm (0.67") • 18mm (0.71") • 19mm (0.75") • 20mm (0.79") • 21mm (0.83") • 22mm (0.87") • 23mm (0.91") • 24mm (0.94") • 25mm (0.98") • 26mm (1.02") • 27mm (1.06") • 28mm (1.1") • 29mm (1.14") • 30mm (1.18") • 31mm (1.22") • 32mm (1.26") • 33mm (1.30") • 34mm (1.34") • 35mm (1.38") • 36mm (1.42") • 37mm (1.46") • 38mm (1.50") • 39mm (1.54") • 40mm (1.57") • 41mm (1.61") • 42mm (1.65") |

No 3-side view is currently available for this product

## **Documents**

No downloads available for this product