

## Boring fixture

### Technical data

|                             |  |
|-----------------------------|--|
| <b>INDEX TRAUB products</b> | G220.3 • TNX200.3 • TNX220.3 •<br>G200.3 • ABC • ABC.2 • ABC65 •<br>C200 • G200.2 • G220 • TNK42/65 •<br>TNX65/42 • C100   |
| <b>Function (Component)</b> | Unscrewing device  |
| <b>Spindle clearance</b>    | 76mm   |
| <b>Bar loading magazine</b> | MBL76 3200 • INDEX MBL76 4200  |
| <b>Machining side</b>       | Main spindle   |
| <b>Material diameter</b>    | 26mm (1.02") • 27mm (1.06") •<br>28mm (1.1") • 29mm (1.14") •<br>30mm (1.18") • 31mm (1.22") •<br>32mm (1.26") • 33mm (1.30") •<br>34mm (1.34") • 35mm (1.38") •<br>36mm (1.42") • 37mm (1.46") •<br>38mm (1.50") • 39mm (1.54") •<br>40mm (1.57") • 41mm (1.61") •<br>42mm (1.65") • 43mm (1.69") •<br>44mm (1.73") • 45mm (1.77") •<br>46mm (1.81") • 47mm (1.85") •<br>48mm (1.89") • 49mm (1.93") •<br>50mm (1.97") • 51mm (2.01") •<br>52mm (2.05") • 53mm (2.09") •<br>54mm (2.13") • 55mm (2.17") •<br>56mm (2.20") • 57mm (2.24") •<br>58mm (2.28") • 59mm (2.32") •<br>60mm (2.36") • 61mm (2.40") •<br>62mm (2.44") • 63mm (2.48") •<br>64mm (2.52") • 65mm (2.56") •<br>66mm (2.60") • 67mm (2.64") •<br>68mm (2.68") • 69mm (2.72") •<br>70mm (2.76") • 71mm (2.80") •<br>72mm (2.83") • 73mm (2.87") •<br>74mm (2.91") • 75mm (2.95") •<br>76mm (2.99") |

No 3-side view is currently available for this product

## **Documents**

No downloads available for this product